

PREFERRED SUPPLIER INFORMATION

NBS REFERENCE M50.

MANUFACTURER:

ALTRO LTD

Works Road, Letchworth Garden City

Hertfordshire, SG6 1NW

Tel: 01462 707600

E-mail: enquiries@altro.com

Website: <http://www.altro.co.uk>

Supplier Contact: Altro Customer Care Centre enquiries@altro.com



PRODUCT DESCRIPTION

ICL APPROVED SPECIFICATION

Range: Altro Wood Smooth

Description: Decorative, flexible, PVC Smooth Flooring.

Application: Areas of use include public circulation areas, school corridors, classrooms, receptions, student accommodation.

Other: Features Altro Easyclean PUR™ Technology providing superior cleanability, significantly reducing cleaning and maintenance costs. Slip Resistance DIN 51130 R10. Suitable for underfloor heating. Can be used with Altro Everlay if a looselay system is required or Altro Acoustic Underlay 1101 to achieve acoustic properties. Fully compatible with Altro Whiterock wall cladding.

Environmental: Achieves a generic BREEAM A+ rating in all Education & Health applications. Contains a bio-plasticiser from a renewable resource

Recyclable: Post-installation clean off-cuts and all factory waste to be recycled by Altro Ltd via Recofloor. Packaging is 100% recyclable.

Warranty: 5 year product guarantee.

TYPICAL NBS SPECIFICATION

M50: 150 PLASTICS FLOORING

Standard: Approved Smooth Flooring to Imperial College London Architectural Standards

Location: To architects finishes schedules.

Base: Sand cement screed or plywood sub base as architects details.

Preparation: Ardex UK Ltd, Arditex smoothing compound or AltroProof epoxy surface damp proof membrane by Altro Ltd

Manufacturer: Altro Ltd, Works Road, Letchworth Garden City, Hertfordshire, SG6 1NW

Range: Altro Wood Smooth

Type: Heterogeneous PVC vinyl to EN ISO 10582. Classification For Use: BS EN 685/EN ISO 10874 class 34 & 43

Width: 2000 mm **Thickness:** 2 mm (EN428/EN ISO 24346) **Format:** Roll

Dimensions: 20m x 2 m (40m²) (EN426/EN ISO 24341) **Weight:** 2.66kg/m² (EN430/EN ISO 23977)

Colour: All colours approved.

Adhesives: AltroFix 365 for dry area.

Seam welding: Hot-welding with matching Altro Welding Rod, as clause 680A

Skirting: Self-coved skirting with Altro CF38R cove former, C7/C8 top edge or Altro Whiterock overlap

Accessories: Clamping drain/channel by Wade International, Visedge VR Edge Strip by Howe Green Ltd.