# Imperial College London

#### **ARCHITECTURAL STANDARDS** PRODUCT DATA SHEET

# M50 FLOOR FINISHES

#### **FLOOR FINISHES**

## M50/150/SHEET 010/11

PREFERED SUPPLIER INFORMATION NBS REFERENCE M50. MANUFACTURER: POLYFLOR LTD PO Box 3, Radcliffe New Road, Whitefield Manchester, M45 7NR, UK Tel: +44 (0)161 767 1111 Fax: +44 (0)161 767 1128 E-mail: info@polyflor.com Website: http://www.polyflor.com Supplier Contact: R Hammond (Contract Sales Representative) rhammond@polyflor.com	
PRODUCT DESCRIPTION ICL APPROVED SPECIFICATION	
Bangal Delugate Standard DUD	

Range: Description:	Polysafe Standard PUR Polysafe Standard PUR is a hugely popular and highly available safety vinyl range combining the assurance of sustainable slip resistance with high durability for years of performance. Available in 16 traditional and clean designs, the range incorporates safety aggregates in the vinyl to create a safe yet attractive interior in commercial or residential settings.
	Polysafe Standard PUR features the exclusive Polysafe PUR reinforcement for optimum appearance retention & superior cleaning
Application:	Ideally suited for heavy traffic areas where there are risks of water spillage and other contaminants in commercial and residential areas such as washrooms, wcs, classrooms and food preparation areas. Typical installations are within education, healthcare, social housing, leisure & commercial office sectors.
Other:	Polysafe Standard PUR fully conforms with HSE & UK Slip Group Guidelines and meets the requirements of the European Safety Flooring Standard - EN 13845, class Esf.
Environmental:	Polysafe Standard PUR achieves BRE Global Environmental Generic A+ rating in major use areas such as education and healthcare.
Recyclable:	Polysafe Standard PUR is 100% recyclable through the Recofloor scheme.
Guarantee:	10 years.
Production:	Manufactured in the UK.

## **TYPICAL NBS SPECIFICATION**

#### M50: 150 SHEETING

Standard:Approved Safety Flooring to Imperial College London Architectural StandardsRange:Polysafe Standard PURManufacturer:POLYFLOR LTD, PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR, UKWidth:2000mm (1500mm at 3.5mm thickness)Thickness:2.0mm, 2.5mm, 3.5mm (EN 428)Format:RollWeight:2430g/m², 3100g/m², 4400g/m² (EN 430)Colour/Pattern:Elmwood (4520) Ash Grey (4540) Cool Aqua (4570) Storm Blue (4560) Autumn Beige (4140) Silver Birch (4020) Cedar Blue (4060) Lilac Blue (4580) Maple Fawn (4030) Alpine Green (4110) Arctic Blue (4130) Nordic Grey (4090) Antique Copper (4120) Redwood (4040) Twilight (4490) Black Walnut (4150)Acoustic Underlay:Polyflor Acoustifoam - a closed cell vinyl foam backing sheet designed to provide impact sound reduction requirements. (and primer if required by manufacturer): Consult with Polyflor Ltd for recommendations and details. Seam welding: Hot-welding with matching Polyflor Welding RodSkirting & Wall First:Coved skirtings, cove former and capping strip - contact Polyflor Ltd for details		
Manufacturer:POLYFLOR LTD, PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR, UKWidth:2000mm (1500mm at 3.5mm thickness)Thickness:2.0mm, 2.5mm, 3.5mm (EN 428)Format:RollWeight:2430g/m², 3100g/m², 4400g/m² (EN 430)Colour/Pattern:Elmwood (4520) Ash Grey (4540) Cool Aqua (4570) Storm Blue (4560) Autumn Beige (4140) Silver Birch (4020) Cedar Blue (4060) Lilac Blue (4580) Maple Fawn (4030) Alpine Green (4110) Arctic Blue (4130) Nordic Grey (4090) Antique Copper (4120) Redwood (4040) Twilight (4490) Black Walnut (4150)Acoustic Underlay:Polyflor Acoustifoam - a closed cell vinyl foam backing sheet designed to provide impact sound reduction requirements. (and primer if required by manufacturer): Consult with Polyflor Ltd for recommendations and details. Seam welding: Hot-welding with matching Polyflor Welding Rod	Standard:	Approved Safety Flooring to Imperial College London Architectural Standards
Width:2000mm (1500mm at 3.5mm thickness)Thickness:2.0mm, 2.5mm, 3.5mm (EN 428)Format:RollWeight:2430g/m², 3100g/m², 4400g/m² (EN 430)Colour/Pattern:Elmwood (4520) Ash Grey (4540) Cool Aqua (4570) Storm Blue (4560) Autumn Beige (4140) Silver Birch (4020) Cedar Blue (4060) Lilac Blue (4580) Maple Fawn (4030) Alpine Green (4110) Arctic Blue (4130) Nordic Grey (4090) Antique Copper (4120) Redwood (4040) Twilight (4490) Black Walnut (4150)Acoustic Underlay:Polyflor Acoustifoam - a closed cell vinyl foam backing sheet designed to provide impact sound reduction requirements. (and primer if required by manufacturer): Consult with Polyflor Ltd for recommendations and details. Seam welding: Hot-welding with matching Polyflor Welding Rod	Range:	Polysafe Standard PUR
Thickness: 2.0mm, 2.5mm, 3.5mm (EN 428)   Format: Roll   Weight: 2430g/m², 3100g/m², 4400g/m² (EN 430)   Colour/Pattern: Elmwood (4520) Ash Grey (4540) Cool Aqua (4570) Storm Blue (4560) Autumn Beige (4140) Silver Birch (4020) Cedar Blue (4060) Lilac Blue (4580) Maple Fawn (4030) Alpine Green (4110) Arctic Blue (4130) Nordic Grey (4090) Antique Copper (4120) Redwood (4040) Twilight (4490) Black Walnut (4150)   Acoustic Underlay: Polyflor Acoustifoam - a closed cell vinyl foam backing sheet designed to provide impact sound reduction requirements.   Adhesive: (and primer if required by manufacturer): Consult with Polyflor Ltd for recommendations and details. Seam welding: Hot-welding with matching Polyflor Welding Rod	Manufacturer:	POLYFLOR LTD, PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR, UK
Format: Roll   Weight: 2430g/m², 3100g/m², 4400g/m² (EN 430)   Colour/Pattern: Elmwood (4520) Ash Grey (4540) Cool Aqua (4570) Storm Blue (4560) Autumn Beige (4140) Silver Birch (4020) Cedar Blue (4060) Lilac Blue (4580) Maple Fawn (4030) Alpine Green (4110) Arctic Blue (4130) Nordic Grey (4090) Antique Copper (4120) Redwood (4040) Twilight (4490) Black Walnut (4150)   Acoustic Underlay: Polyflor Acoustifoam - a closed cell vinyl foam backing sheet designed to provide impact sound reduction requirements.   Adhesive: (and primer if required by manufacturer): Consult with Polyflor Ltd for recommendations and details. Seam welding: Hot-welding with matching Polyflor Welding Rod	Width:	2000mm (1500mm at 3.5mm thickness)
Weight: 2430g/m², 3100g/m², 4400g/m² (EN 430)   Colour/Pattern: Elmwood (4520) Ash Grey (4540) Cool Aqua (4570) Storm Blue (4560) Autumn Beige (4140) Silver Birch (4020) Cedar Blue (4060) Lilac Blue (4580) Maple Fawn (4030) Alpine Green (4110) Arctic Blue (4130) Nordic Grey (4090) Antique Copper (4120) Redwood (4040) Twilight (4490) Black Walnut (4150)   Acoustic Underlay: Polyflor Acoustifoam - a closed cell vinyl foam backing sheet designed to provide impact sound reduction requirements.   Adhesive: (and primer if required by manufacturer): Consult with Polyflor Ltd for recommendations and details. Seam welding: Hot-welding with matching Polyflor Welding Rod	Thickness:	2.0mm, 2.5mm, 3.5mm (EN 428)
Colour/Pattern: Elmwood (4520) Ash Grey (4540) Cool Aqua (4570) Storm Blue (4560) Autumn Beige (4140) Silver Birch (4020) Cedar Blue (4060) Lilac Blue (4580) Maple Fawn (4030) Alpine Green (4110) Arctic Blue (4130) Nordic Grey (4090) Antique Copper (4120) Redwood (4040) Twilight (4490) Black Walnut (4150)   Acoustic Underlay: Polyflor Acoustifoam - a closed cell vinyl foam backing sheet designed to provide impact sound reduction requirements.   Adhesive: (and primer if required by manufacturer): Consult with Polyflor Ltd for recommendations and details. Seam welding: Hot-welding with matching Polyflor Welding Rod	Format:	Roll
Acoustic Underlay: Polyflor Acoustifoam - a closed cell vinyl foam backing sheet designed to provide impact sound reduction requirements.   Adhesive: (and primer if required by manufacturer): Consult with Polyflor Ltd for recommendations and details. Seam welding: Hot-welding with matching Polyflor Welding Rod	Weight:	2430g/m², 3100g/m², 4400g/m² (EN 430)
Adhesive: (and primer if required by manufacturer): Consult with Polyflor Ltd for recommendations and details. Seam welding: Hot-welding with matching Polyflor Welding Rod	Colour/Pattern:	Blue (4580) Maple Fawn (4030) Alpine Green (4110) Arctic Blue (4130) Nordic Grey (4090) Antique Copper (4120) Redwood (4040)
matching Polyflor Welding Rod	Acoustic Underlay:	Polyflor Acoustifoam - a closed cell vinyl foam backing sheet designed to provide impact sound reduction requirements.
Skirting & Wall Finishes: Coved skirtings, cove former and capping strip - contact Polyflor Ltd for details	Adhesive:	