Imperial College

London

ARCHITECTURAL STANDARDS PRODUCT DATA SHEET

M50 FLOOR FINISHES

FLOOR FINISHES

M50/150/SHEET 011/11


PREFERED SUPPLIER INFORMATION

NBS REFERENCE M50. MANUFACTURER: POLYFLOR LTD

PO Box 3, Radcliffe New Road, Whitefield

Manchester, M45 7NR, UK
Tel: +44 (0)161 767 1111
Fax: +44 (0)161 767 1128
E-mail: info@polyflor.com
Website: http://www.polyflor.com

Supplier Contact: R Hammond (Contract Sales Represntative) rhammond@polyflor.com



PRODUCT DESCRIPTION

ICL APPROVED SPECIFICATION

Range: Polysafe Vogue Ultra PUR

Description: Polysafe Vogue Ultra PUR is a hugely popular and highly available safety vinyl range combining the assurance of sustainable slip

resistance with high durability for years of performance. Available in 16 traditional colours with a multi-coloured chip decoration, the range

incorporates safety aggregates in the vinyl to create a safe yet attractive interior in commercial or residential settings.

Polysafe Vogue Ultra PUR features the exclusive Polysafe PUR reinforcement for optimum appearance retention & superior cleaning

Application: deally suited for heavy traffic areas where there are risks of water spillage and other contaminants in commercial and residential areas

such as washrooms, wcs, classrooms and food preparation areas. Typical installations are within education, healthcare, social housing,

leisure & commercial office sectors.

Other: Polysafe Vogue Ultra PUR fully conforms with HSE & UK Slip Group Guidelines and meets the requirements of the European Safety

Flooring Standard - EN 13845, class Esf.

Environmental: Polysafe Vogue Ultra PUR achieves BRE Global Environmental Generic A+ rating in major use areas such as education and healthcare.

Recyclable: Polysafe Vogue Ultra PUR is 100% recyclable through the Recofloor scheme.

Guarantee: 10 years.

Production: Manufactured in the UK.

TYPICAL NBS SPECIFICATION

M50: 150 SHEETING

Standard: Approved Safety Flooring to Imperial College London Architectural Standards

Range: Polysafe Vogue Ultra PUR

Manufacturer: POLYFLOR LTD, PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR, UK

Width: 2000mm

Thickness: 2.0mm (EN 428)

Format: Roll

Weight: 2400g/m² (EN 430)

Colour/Pattern: Chambray (5083) Steelwool (5082) Linen (5081) Light Concrete (5087) Dark Concrete (5089) Cement (5088) Frosted Silver (5084)

Brushed Titanium (5086) Sand Grain (5085) Flagstone Grey (5091) Clay Stone (5092) Crema Nova (5090)

Acoustic Underlay: Polyflor Acoustifoam - a closed cell vinyl foam backing sheet designed to provide impact sound reduction requirements.

Adhesive: (and primer if required by manufacturer): Consult with Polyflor Ltd for recommendations and details. Seam welding: Hot-welding with

matching Polyflor Welding Rod

Skirting & Wall Finishes: Coved skirtings, cove former and capping strip - contact Polyflor Ltd for details